

Drawing # S-0602-03-02

MI Cable Technologies, Inc.

Bay 6, 5905 - 11 Street SE

Calgary, Canada

T2H 2A6

Tel: 403-571-8266


Fax: 403-571-8267

email: sales@micabletechnologies.com

19/08/2010

Six Wire RTD Cable Design Specifications, C7 Series, Type Y Sheath

Cable Diameter (D)	(inch)	0.118	0.125	0.177	0.188	0.236	0.250	0.313	0.375
	(mm)	3.0	3.2	4.5	4.8	6.0	6.4	8.0	9.5
Wire Diameter (W)	(inch)	0.012	0.013	0.019	0.020	0.025	0.027	0.033	0.040
	(mm)	0.30	0.33	0.48	0.51	0.64	0.69	0.84	1.02
Sheath Thickness (t)	(inch)	0.013	0.014	0.020	0.021	0.027	0.029	0.036	0.043
	(mm)	0.33	0.36	0.51	0.53	0.69	0.74	0.91	1.09
Bolt Circle Diameter (b)	(inch)	0.060	0.063	0.089	0.094	0.119	0.126	0.158	0.189
	(mm)	1.52	1.60	2.26	2.39	3.02	3.20	4.01	4.80
Coil Length	(feet)	1900	1700	850	750	470	420	270	180
	(m)	579	518	259	229	143	128	82	55
IR Test Voltage	VDC	500	500	500	500	500	500	500	500
Dielectric Test Voltage	VAC	500	500	500	500	750	750	750	750



Cable dimensions shown are nominal. Actual dimensions may vary within tolerance limits.
Specifications subject to change without notice.